

SACP 2x5516

1710 -2170 MHz Dual (2x) CP log-periodic antenna

Features

- ❑ **Transmit Diversity Gain**
- ❑ **Can be configured to combine space & polarization diversity**
- ❑ **Outstanding performance over the entire band (1710 - 2170 MHz)**
- ❑ **Excellent Axial Ratio**
- ❑ **Optimized for 4G & 3G systems**
- ❑ **Low intermodulation**
- ❑ **Improved Side-to-side rejection**
- ❑ **Fading reduction**
- ❑ **Excellent isolation between ports**



Electrical specifications

Frequency range:	1710-2170 MHz
Impedance:	50 ohm
Connector type:	7/16 Din
Return loss:	18 dB
Polarization:	Circular
Gain ea. port [Circular]:	2x16 dBdC
Gain ea. port [Linear]:	2x13 dBdL
Axial Ratio:	2 dB
Isolation between ports (TX band):	28 dB
Front-to-back ratio:	30 dB
Intermodulation (2x20W):	IM3 150 dB IM5 160 dB IM7/9 170 dB
Power rating:	2x 300 W
H-plane (-3 dB point):	2x 55°
V-plane (-3 dB point):	2x 7°
Lightning protection:	DC grounded

Mechanical specifications

Overall height:	56 in	[1422 mm]
Width:	9.7 in	[246 mm]
Depth:	5.5 in	[140 mm]
Weight (excluding brackets):	16 lbs	[7.2 Kg]
Wind load measured up to:	150 mph	[240 Km/h]
Wind area (front of antenna):	3.76 sq. ft.	[0.35 sq.m]
Lateral thrust at 113 mph/ 180 Km/h (worst case):	192 lbs	[855 N]

Materials

Radiating Elements:	Silver plated brass
Transformer (Power distribution)	Ceramic PCB
Chassis:	Aluminum
Radome:	PVC/TPO
Mounting bolts:	Stainless steel

The SACP 2x5516 is made in the U.S.A.