

# SACP 4x5514

1710 -2170 MHz quad (4x) CP log-periodic antenna

## Features

- ❑ Transmit Diversity Gain
- ❑ Can be configured to combine space & polarization diversity
- ❑ Outstanding performance over the entire band (1710 - 2170 MHz)
- ❑ Excellent Axial Ratio
- ❑ Optimized for 4G & 3G systems
- ❑ Low intermodulation
- ❑ Improved Side-to-side rejection
- ❑ Fading reduction
- ❑ Excellent isolation between ports



## Electrical specifications

Frequency range:	<b>1710-2170 MHz</b>
Impedance:	<b>50 ohm</b>
Connector type:	<b>7/16 Din</b>
Return loss:	<b>18 dB</b>
Polarization:	<b>Circular</b>
Gain ea. port [Circular]:	<b>4x14 dBdC</b>
Gain ea. port [Linear]:	<b>4x11 dBdL</b>
Axial Ratio:	<b>2 dB</b>
Isolation between ports (TX band):	<b>28 dB</b>
Front-to-back ratio:	<b>30 dB</b>
Intermodulation (2x20W):	<b>IM3 150 dB</b> <b>IM5 160 dB</b> <b>IM7/9 170 dB</b>
Power rating:	<b>2x 300 W</b>
H-plane (-3 dB point):	<b>2x 55°</b>
V-plane (-3 dB point):	<b>2x 15°</b>
Lightning protection:	<b>DC grounded</b>

## Mechanical specifications

Overall height:	<b>56 in</b>	<b>[1422 mm]</b>
Width:	<b>9.7 in</b>	<b>[246 mm]</b>
Depth:	<b>5.5 in</b>	<b>[140 mm]</b>
Weight (excluding brackets):	<b>16 lbs</b>	<b>[7.2 Kg]</b>
Wind load measured up to:	<b>150 mph</b>	<b>[240 Km/h]</b>
Wind area (front of antenna):	<b>3.76 sq. ft.</b>	<b>[0.35 sq.m]</b>
Lateral thrust at 113 mph/ 180 Km/h (worst case):	<b>192 lbs</b>	<b>[855 N]</b>

## Materials

Radiating Elements:	<b>Silver plated brass</b>
Transformer (Power distribution)	<b>Ceramic PCB</b>
Chassis:	<b>Aluminum</b>
Radome:	<b>PVC/TPO</b>
Mounting bolts:	<b>Stainless steel</b>

*The SACP 4x5514 is made in the U.S.A.*