

The leader in CP-LOG. Antennas

SNCP 2x5510

5100-5900 MHz 2 port CP-LOG antenna

SNCP 2x5510 **2 port 5100-5900** MHz

- Transmit Diversity
- Excellent Axial Ratio
- Improved Side-to-side rejection
- Optimized for 5G & 4G systems
- Fading reduction
- Outstanding isolation between ports

Electrical specifications	
Frecuncy(MHz):	5100-5900
Polarization:	Circular
No of Ports:	2
Connector type:	4.3-10
Gain (dBi):	10
H-plane:	50°
V-plane:	35°
Power rating (W):	30
Axel ratio (dB):	2
Impedence (Ω):	50
Return loss (dB):	20
FTB (dB):	30
Lightning protection:	DC Ground
Operating temperature:	-40° to +140° F [-40° to +60° C]
Mechanical specifications	
Overall height:	6.8 in 173 mm
Width:	4.2 in 107 mm
Depth:	3.8 in 97 mm
Weight (exluding brackets):	3 lbs 1.4 Kg
Wind load measured up to:	150 mph 240 km/h
Wind area (front of antenna):	0.2 sq.ft. 0.018 sq.m.
Lateral Thrust at 113 mph / 180 Km/h (worst case):	10 lbs 45 N
Materials	
Radiaing elements	Ceramic PCB & silverplated brass
Transformer :	Ceramic PCB
Tray:	Aluminum
Radome:	PVC / TPO
<i>The SNCP 2x5510 is made in the U.S.A.</i>	

