

The leader in CP-LOG. Antennas

SACPC 4x36006

1710 - 2250 MHz (1 sector 4 port omni) CP-LOG antenna

SACPC 4x36010 4 port 1710-2250 MHz Canister antenna

- Transmit Diversity
- Excellent Axial Ratio
- Low intermodulation
- Improved Side-to-side rejection
- Outstanding indoor penetration

Electrical specifications		
Frequency (MHz):	1710-2250	
Polarization:	Circular	
No of Ports:	4	
Connector type:	7/16 Din or 4.3-10	
Gain (dBi):	8	
H-plane:	360°	
V-plane:	35°	
Power rating (W):	150	
Axel ratio (dB):	2	
Impedance (Ω):	50	
Return loss (dB):	20	
FTB (dB):	30	
Port to port [in-band TX]	28	
IM3 (dBc):	153	
IM5 (dBc):	160	
IM7/9 (dBc):	170	
Lightning protection:	DC Ground	
Operating temperature:	-40° to +140° F [-40° to +60° C]	
Mechanical specifications		
Overall height:	24 in	610 mm
Diameter:	14 in	355 mm
Volume:	2.15 cu ft.	0.06 m3
Weight (exluding brackets):	28 lbs	12.6 Kg
Wind load measured up to:	150 mph	240 km/h
Wind area (front of antenna):	2.33 sq.ft.	0.22 sq.m.
Lateral Thrust at 113 mph / 180 Km/h (worst case):	120 lbs	530 N
Materials		
Radiating elements:	silverplated brass	
Transformer :	Ceramic PCB	
Tray:	Aluminum	
Radome:	PVC / TPO	
Antenna bolts:	Stainless Steel	
<i>The SACPC 4x36008 is made in the U.S.A.</i>		

